

—Specifications

- **4 x RTL8168G, 10/100/1000M Gigabit Ethernet (POE+) ports**
- **Supports PCI Express Specification Revision 2.1**
- **Support IEEE 802.3at for PoE+ (Power over Ethernet Plus)**
- **Power Sourcing Equipment (PSE) design, provides data and up to 65W of power on four ethernet ports**
- **Supports jumbo frame to 9K bytes**
- **Power Input for POE (12V)**
 - IDE Power (J1): Max. 60W / SATA Power (J2): Max. 48 W
6pin power Connector (J3): Max. 70 W
- **OS지원**
 - Windows XP/ Vista/ 7/ 8/ 8.1, Server 2003/2008/ 2012
 - Linux kernel 3.x /2.6.x/ 2.4.x, FreeBSD 7.x and 8.0, SCO OpenServer 6
UnixWare 7.1.x ,SCO Unix 5.0.6 /5.0.7
 - Novell Server 5.x and 6.x
 - Mac OS 10.4/10.5/10.6/10.7 on Intel-based Mac computer
- **인증서**
 - KCC / CE / FCC / VCCI / RCM
- **제품크기**
 - 101mm(H) x 151.5mm(L) / NW: 151g
- **제품구성**
 - GEPX4-PCIE4XE301
 - Driver CD